

MODULAR COMPACT DISTRIBUTION SYSTEM FOR DOMESTIC WATER SYSTEMS

K-BLOC
MODULAR SYSTEM

EASY AND FAST TO INSTALL
COMPACT AND STRONG
FUNCTIONAL DESIGN
FULL RANGE



FIND OUT MORE

INSTALLATION IS A GAME FOR PROFESSIONALS




MODULAR COMPACT DISTRIBUTION SYSTEM FOR DOMESTIC WATER SYSTEMS



EASY AND FAST TO INSTALL

Module preparation is simplified by the TECOFIX fixing system and can easily be performed off-site. Each module can be connected to pipes or system components via the FASTEC connection system, which guarantees fast, secure connections.

The solid module fixing becomes a reference point for anchoring the system to the structure.




COMPACT AND STRONG

All components have been designed to maximise compactness, facilitating installation in tight spaces.




FUNCTIONAL DESIGN

The K-BLOC system and all its components have been designed to maximise efficiency, utility and convenience. The functional design offers neat installation that emphasises the installer's professionalism.



FULL RANGE

A wide selection of modules, manifolds, valves and fittings are able to meet a variety of system requirements, in both new buildings and renovations.




TECOFIX INSTALLATION COMPONENTS
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



TECOFIX K-BLOC fastening modules

TECOFIX modular fixing plate



Code	Description	Pack
TXA01	TECOFIX modular fixing plate	18

TECOFIX flush-mounting box

- Includes:**
- Site protection cover
 - Fixing mounts




Code	Description	Pack
TXA02	Box for flush-mounting applications	8

K-BLOC TECOFIX support brackets

Tecofix fixing brackets


- Includes:**
- Expansion plugs
 - Fixing screws



Code	Description	Compatibility	Pack
TX001	TECOFIX HIGH brackets kit	CK3-CK2 manifolds T4, T4 ∈ T-valves	10
TX002	TECOFIX LOW brackets kit	CK3-CK2 manifolds T4, T4 ∈ T-valves	10
TX003	TECOFIX brackets kit FOR STRAIGHT VALVES	T4 ∈ straight valves	10
TX004	TECOFIX brackets kit FOR METERS	Kit for meters	10

K-BLOC fixing kit TECOFIX


Suitable for hot and cold water systems



- Includes:**
- N° 2 TXA01 Modular fixing plates
 - N° 1 TX001 TECOFIX HIGH brackets kit
 - N° 1 TX002 TECOFIX LOW brackets kit
 - Expansion plugs
 - Fixing screws

Code	Description	Compatibility	Pack
TX005	Kit for manifold and valves	CK3-CK2 manifolds T4 valves, T-valves	5

E03 Faceplate with magnetic closure for flush-mounting box




- Includes:**
- Fixing screws

Code	Finish	Pack
KPLE0301600	White	5
KPLE0301M00	Polished chrome	1
KPLE0301800	Silver	1
KPLE0301A00	Black Soft Touch	1

TECOFIX INSTALLATION COMPONENTS
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



CK3 multiple shut-off manifolds



Technical data:

- +5 °C ÷ +95 °C
- PN 10 (10 bar)
- DIN EN 13828, W570-1, KTW-BWGL, ACS, PZH

Includes:

- 1 DN15 manifold with DN10 individual shut-off valves
- Stickers for utility identification


Does not include:

- TECOFIX fixing components
- Fastec fittings (page 58)

Code	Outlets	L (mm)	Connections	TECOFIX brackets compatibility	Pack
			FASTEC®		
CK032F10100	2	87	F13		5
CK033F10100	3	119	F13		5
CK034F10100	4	151	F13		5
CK035F10100	5	183	F13		5
CK036F10100	6	215	F13		5

[See page 58](#)

CK2 manifolds without shut-off valves



Technical data:

- +5 °C ÷ +95 °C
- PN 16 (16 bar)
- KTW-BWGL

Includes:

- 1 DN15 manifold
- Stickers for utility identification

Does not include:

- TECOFIX fixing components
- Fastec fittings (page 58)

Code	Outlets	L (mm)	Connections	TECOFIX brackets compatibility	Pack
			FASTEC®		
CK023F10100	3	119	F13		5
CK024F10100	4	151	F13		5
CK025F10100	5	183	F13		5

[See page 58](#)

Spare parts for CK3

See page 164, or visit the website for all product information.



T4 "Top Entry" ball valve, "T" version



Technical data:

- +5 °C ÷ +95 °C
- PN 10 (10 bar)
- DIN EN 13828, W570-1, KTW-BWGL, ACS, PZH

Includes:

- 1 valve with removable ball and control handle

Does not include:

- TECOFIX fixing components
- Fastec fittings (page 58)
- € 100 electric actuator (page 57)

Code	DN	Connections	Kv*	TECOFIX brackets compatibility	Pack
		FASTEC®			
T4P12C2100	DN10	F13 F / F / M	4,0		5
T4P32C1100	DN15	F13 F / F / F	- 5,8		10
T4P32C2100	DN15	F13 F / F / M	- 5,8		10
T4P32C3100	DN15	F13 M / F / F	- 5,8		10
T4P3211100	DN15	-	Rp 1/2" F / F		5
T4P3271100	DN15	F13 F / F	- 15		10
T4P3272100	DN15	F13 F / M	- 15		10

[See page 58](#)

* The coefficient Kv defines the water flow (in m³/h from 5 °C to 40 °C) through a valve with a differential pressure of 1 bar.

Spare parts for T4€

See page 171, or visit the website for all product information.



TECOFIX INSTALLATION COMPONENTS
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



Valve and fitting kit for meter



Technical data:

- +5 °C ÷ +90 °C
- PN 10 (10 bar)
- DIN EN 13828 , W570-1 , KTW-BWGL , ACS , PZH

Includes:

- 1 valve with removable ball and control handle with optional motor
- Fitting with non-return valve on the outlet

Does not include:

- TECOFIX fixing components
- Fastec fittings (page 58)
- Volumetric meter and its communication modules
- Joints
- €100 electric actuator (page 57)

Kit code	DN	Connections	TECOFIX brackets compatibility	Pack
		D1 FASTEC®		
CKCCXF10100	DN15	F13 F	 TX004 kit	5
See page 58				

Volumetric meter



Code	Description	DN.	Pack
KA00CC0005	SJ EVO meter - Q ₃ 2.5 m ³ /h - L. 80 mm - G 3/4" Suitable for operation with hot and cold water	15	1

Joint



Code	Description	Pack
KA00CC0007	Joint L. 80 mm	5
KA00CC0008	Joint L. 110 mm	5

Spare parts for valve and fitting kit for meter

See page 166, or visit the website for all product information.

€100 ON/OFF electric actuator




Includes:

- €100 ON/OFF electric actuator
- 1.25 m cable with Molex Micro-Fit connector

Code	Voltage	Auxiliary microswitch position	Pack
E1045100	AC 110 – 230 V	With valve closed	1
E1046100	AC/DC 24 V		
Code	Voltage	Auxiliary microswitch position	Pack
E1042100	AC 110 – 230 V	With valve open (zone valve)	1
E1044100	AC/DC 24 V		

Optional 3 metre cable for €100 electric actuator



Code	Description	Pack
KA00K00014	Kit of 6P X 3M cable + Micro-Fit connector	1

Communication modules for remote meter reading

The volumetric meter can be equipped with communication modules for remote metering.



Code	Description	Pack
KA00CC0001	EVO 868 MHz LoRaWAN Radio Module	1
KA00CC0002	EVO 868 MHz Wireless M-Bus Radio Module	1
KA00CC0003	M-Bus EVO module	1
KA00CC0004	Pulse Evo module	1

TECOFIX INSTALLATION COMPONENTS
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



Fastec adapters and fittings

Fastec Fittings

Code	Description	Pack
RF12210200	90° F / F	10
RF12210100	90° M / F	10
RF12310200	T F / F / F	5
RF12310100	T M / F / F	5
RF12110200	Sleeve F / F	10
KA00K00008	Nipple M / M	10
KA00F10001	Dual joint Twin F / F / M	5
KA00K00016	Plug F	10
KA00K00002	Plug M	20
RF12110400	Barrel nut M L. 25 mm	10
RF12110500	M L. 50 mm	10
RF12110600	M L. 75 mm	8

Threaded fittings

Code	Description	Pack
KA00K00003	M x R 1/2"	10
KA00K00013	M x R 3/4"	10
RF12101000	M x Rp 1/2"	10
RF12111000	M x Rp 3/4"	10
KA00K00004	EUROKONUS M x EK 3/4"	10
RF122F0100	M 90° x R 1/2"	10
RF122F0200	M 90° x Rp 1/2"	10
RF12110900	SWIVEL NUT FLAT SEAL WITH O-RING M x G 3/4"	10

R (male) and Rp (female) threaded connections in accordance with EN 10226-1 and G threaded connections in accordance with ISO 228-1.

Fittings for PEX pipes

Code	Pipe Ø x Thickness	Pack
RF12100100	M 16 x 1.8	10
RF12100200	M 20 x 1.5	10
RF12100300	M 25 x 2.3	5
RF13M1210301	M 12 x 1.1	10
RF13M1610301	M 16 x 1.5	10
RF13M2010301	M 20 x 1.9	10
RF13M1210401	M 12 x 1.1	10
RF13M1610401	M 16 x 1.5	10
RF13M2010401	M 20 x 1.9	10

FASTEC semi-rigid corrugated stainless steel pipe

Code	Description	Pack
RF12710100	M L. 250 mm	1
RF12710200	M L. 400 mm	1

Fittings for multi-layer pipes


Code	Pipe Ø x Thickness	Pack	Code	Pipe Ø x Thickness	Pack
RF13M16101VA	M 16 x 2.0	10	511115MP	M 16 x 2.0	5
RF13M16102VA	M 16 x 2.25	10	511116MP	M 16 x 2.25	5
RF13M20101VA	M 20 x 2.0	10	511118MP	M 20 x 2.0	5
RF13M20102VA	M 20 x 2.5	10	511119MP	M 20 x 2.25	5
RF13M26101VA	M 26 x 3.0	5	511120MP	M 20 x 2.5	5
1651039	M 16 x 2.0	10	511121MP	M 25 x 2.5	5
1651040	M 20 x 2.0	10	511122MP	M 26 x 3.0	5
1651041	M 26 x 3.0	5	39342	M 16 x 2.0	10
			39344	M 20 x 2.0	10

Fittings with FASTEC connection available in manufacturers' catalogues

COMISA COMISA PRESS Pipe Ø 16-20	HENCO Pipe Ø 16-20-26	APE raccordi AP SERIES Pipe Ø 16-20-26	+GF+ ALUPEX EXPRESS Pipe Ø 16-20	JRG SANIPEX MT Pipe Ø 16-20	TECE LOGO Pipe Ø 20	FLEX Pipe Ø 16-20-25
---	---------------------------------	---	---	--------------------------------	----------------------------------	-------------------------

EXTENDER telescopic joint


Code	Description	Pack
RF12110300	EXTENDER telescopic joint F / F	5



FASTEC®
THE FAST AND SECURE PLUMBING CONNECTION

Plumbing connection with pin locking (page 6).

F13 DN 15 Equivalent to 1/2"




1. Insert the fitting with the pin raised.
2. Lower the locking pin to complete the connection.


APPLICATION EXAMPLES
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



MULTIPLE SHUT-OFF MANIFOLD




FINAL COMPOSITION VIEW




CK3 Multiple shut-off manifold	
x1	5-way CK035F10100
x1	6-way CK036F10100

FLUSH-MOUNTING MANIFOLD WITH GENERAL SHUT-OFF VALVES




MANIFOLD CONNECTION




APPLICATION EXAMPLES
FOR K-BLOC MODULAR COMPACT DISTRIBUTION SYSTEM



FLUSH-MOUNTING MANIFOLD WITH T-VALVE



STRAIGHT MOTORISED VALVES



METER UNIT

